

SAFETY DATA SHEET

1. Identification

Product identifier	INSWOOL 2300 PAPER; INSWOOL 2300 PLEATED MODULES; INSWOOL 2300 VENEERING MODULES	
Other means of identification		
Brand Code	5819, 687B, 676B, 0411, 268C, 449B, 0525, 0223, 096B, 367A, 440A, 726C	
Synonyms	INSWOOL 2300 PAPER * INSWOOL 2300 PAPER GASKET * INSWOOL 2300 PLEATED MODULE 8, 9.3, 10, 10.7, 12# DENSITY * INSWOOL 2300 VENEERING MODULE 8#, 9.3# * INSWOOL EDGE GRAIN 2300 MODULE * INSWOOL 2300 PAPER H	
Recommended use	For Industrial Use Only	
Recommended restrictions	Avoid dry cutting, blasting, or dust generation.	
Manufacturer/Importer/Supplier	r/Distributor information	
Manufacturer		
Company name	HarbisonWalker International	
Address	1305 Cherrington Parkway, Suite 100	
	Moon Township, Pennsylvania 15108 US	
Telephone	General Phone: 412-375-6600	
Website	www.thinkHWI.com	

Emergency phone number 2. Hazard(s) identification

Physical hazards	Not classified.	
Health hazards	Carcinogenicity	Category 2
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	

Not available.

Label elements



Signal word	Warning
Hazard statement	Suspected of causing cancer.
Precautionary statement	
Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection. Wear protective gloves/protective clothing/eye protection/face protection.
Response	If exposed or concerned: Get medical advice/attention.
Storage	Store in a manner to minimize airborne dust.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Aluminosilicate Refractory Ceran Fiber	mic Refractory Ceramic Fiber/Fibre (RCF) High Temperature Insulation Wool (HTIW) Synthetic Vitreous Fiber (SVF) Man-Made Mineral Fiber (MMMF) Man-Made Vitreous Fiber (MMVF) Alumino Silicate Wool (ASW)	142844-00-6	80 - 100
Aluminium Oxide (Non-Fibrous)		1344-28-1	2.5 - 10
Glass, Oxide, Chemicals		65997-17-3	2.5 - 10
Other components below reporta			2.5 - 10
Composition comments	This product contains Refractory Ceramic Fibers (classified RCFs as a possible human carcinogen, sufficient evidence of carcinogenicity in animals ar respirable RCFs as reasonably anticipated carcino study was issued in 2017 (LeMasters et al., in pre follow-up, no excess of lung cancers in the mortali radiographic findings of interstitial fibrosis were fou found a small incidence of other effects that appea report did not change the current hazard classifica handling methods are followed, including air monit airborne fibers, minimizing airborne exposures thro wearing protective clothing, gloves, and eye protect www.htiwcoalition.org Please review the workplace	Group 2B. This classificat d no available data in hu gens. The final report of ss). The study concluded y study and no significan nd in this group of worke r unrelated to RCF exposi- tion for RCF. HWI recon- pring in areas wherever the ough use of NIOSH appro- tion. For additional inform	tion was based on mans. NTP classified the USA mortality d that "after 30 years of t association with rs." The study also sure. The final mortality mends that safe he potential exists for oved respirators, and nation please visit
4. First-aid measures			
Inhalation	Move to fresh air. Call a physician if symptoms dev	elop or persist.	
Skin contact	Wash off with soap and water. Get medical attention	on if irritation develops an	d persists.
Eye contact	Rinse with water. Get medical attention if irritation	develops and persists.	
Ingestion	Rinse mouth. Get medical attention if symptoms of		
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irrit	ation.	
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat syn Symptoms may be delayed.	nptomatically. Keep victir	n under observation.
General information	Wash with soap and water before eating, drinking,	smoking or using toilet.	
5. Fire-fighting measures			
Suitable extinguishing media	Use fire-extinguishing media appropriate for surrou	inding materials.	
Unsuitable extinguishing media	Not available.		
Specific hazards arising from the chemical	Not applicable.		
Special protective equipment and precautions for firefighters	Not available.		
6. Accidental release measures			
Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Wear appropr clean-up.	iate protective equipment	and clothing during
Methods and materials for containment and cleaning up	Stop the flow of material, if this is without risk. Follo Put material in suitable, covered, labeled contained SDS.		
Environmental precautions	Avoid discharge into drains, water courses or onto	the ground.	
7. Handling and storage			
Precautions for safe handling	Do not handle until all safety precautions have bee exposure. Should be handled in closed systems, if appropriate personal protective equipment. Observ	possible. Provide adequa ve good industrial hygiene	ate ventilation. Wear e practices.
Conditions for safe storage, including any incompatibilities	Store in tightly closed container. Store away from i SDS).	ncompatible materials (se	ee Section 10 of the

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Components	Туре	Value	Form
Aluminosilicate Refractory Ceramic Fiber (CAS 142844-00-6)	TWA	15 mg/m3	Total dust
US. OSHA Table Z-1 Limits f Components	for Air Contaminants (29 CFR 1910.1 Type	000) Value	Form
Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
US. OSHA Table Z-3 (29 CFF Components	R 1910.1000) Type	Value	Form
Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
US. ACGIH Threshold Limit	Values		
Components	Туре	Value	Form
Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1)	TWA	1 mg/m3	Respirable fraction.
US. NIOSH: Pocket Guide to	Chemical Hazards		
Components	Туре	Value	Form
Aluminosilicate Refractory Ceramic Fiber (CAS 142844-00-6)	TWA	5 fibers/cm3	Respirable Fibrous dus
		0.5 mg/m3	Fiber, total
logical limit values	No biological exposure limits noted for	or the inaredient(s).	
	Recommended Exposure Guideline 0.5 Fiber/CC There is no specific regulatory standard for RCF in the U.S. OSHA's "Particulate Not Otherwise Regulated (PNOR)" standard [29 CFR 1910.1000, Subpart Z, Air Contaminants] applies generally; Total Dust 15 mg/m3; Respirable Fraction 5 mg/m3. The High Temperature Insulation Wool Coalition (HTIW) has sponsored comprehensive toxicology and epidemiology studies to identify potential RCF-related health effects [see Section 11 for more details], consulted experts familiar with fiber and particle science, conducted a thorough review of the RCF-related scientific literature, and further evaluated the data in a state-of-the-art quantitative risk assessment. Based on these efforts and in the absence of an OSHA PEL, HTIW has adopted a recommended exposure guideline, as measured under NIOSH method 7400B. The manufacturers' REG is intended to promote occupational health and safety through prudent exposure control and reduction and it reflects relative technical and economic feasibility as determined by extensive industrial hygiene monitoring efforts undertaken pursuant to an agreement with the U.S. Occupational Safety and Health Administration (OSHA). OTHER OCCUPATIONAL EXPOSURE LEVELS (OEL) Non-regulatory OEL decisions also vary. The evaluation of occupational exposure limits and determining their relative applicability to the workplace is best performed, on a case-by-case basis, by a qualified Industrial Hygienist. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation,		
propriate engineering	Recommended Exposure Guideline (RCF in the U.S. OSHA's "Particulate 1910.1000, Subpart Z, Air Contamina Fraction 5 mg/m3. The High Temperature Insulation Wo and epidemiology studies to identify p details], consulted experts familiar wit the RCF-related scientific literature, a risk assessment. Based on these effor a recommended exposure guideline, manufacturers' REG is intended to pr exposure control and reduction and it determined by extensive industrial hy agreement with the U.S. Occupationa OCCUPATIONAL EXPOSURE LEVE evaluation of occupational exposure I workplace is best performed, on a ca Good general ventilation (typically 10	0.5 Fiber/CC There is no spec Not Otherwise Regulated (PNC ants] applies generally; Total Du ol Coalition (HTIW) has sponse botential RCF-related health eff th fiber and particle science, co and further evaluated the data in orts and in the absence of an O as measured under NIOSH me romote occupational health and t reflects relative technical and regione monitoring efforts undert al Safety and Health Administra ELS (OEL) Non-regulatory OEL limits and determining their rela- se-by-case basis, by a qualified air changes per hour) should b	DR)" standard [29 CFR ist 15 mg/m3; Respirable ored comprehensive toxicol- ects [see Section 11 for mo nducted a thorough review in a state-of-the-art quantita SHA PEL, HTIW has adopt thod 7400B. The safety through prudent economic feasibility as aken pursuant to an tion (OSHA). OTHER decisions also vary. The tive applicability to the Industrial Hygienist.
propriate engineering	Recommended Exposure Guideline (RCF in the U.S. OSHA's "Particulate 1910.1000, Subpart Z, Air Contamina Fraction 5 mg/m3. The High Temperature Insulation Wo and epidemiology studies to identify p details], consulted experts familiar wit the RCF-related scientific literature, a risk assessment. Based on these effor a recommended exposure guideline, manufacturers' REG is intended to pr exposure control and reduction and it determined by extensive industrial hy agreement with the U.S. Occupationa OCCUPATIONAL EXPOSURE LEVE evaluation of occupational exposure I workplace is best performed, on a ca Good general ventilation (typically 10	0.5 Fiber/CC There is no spec Not Otherwise Regulated (PNC ants] applies generally; Total Du ol Coalition (HTIW) has sponse botential RCF-related health eff th fiber and particle science, co and further evaluated the data in orts and in the absence of an O as measured under NIOSH me romote occupational health and the reflects relative technical and giene monitoring efforts undert al Safety and Health Administra ELS (OEL) Non-regulatory OEL limits and determining their relative se-by-case basis, by a qualified air changes per hour) should b pplicable, use process enclosu tain airborne levels below recon ished, maintain airborne levels	DR)" standard [29 CFR ist 15 mg/m3; Respirable ored comprehensive toxicolo ects [see Section 11 for mo nducted a thorough review in a state-of-the-art quantitat SHA PEL, HTIW has adopt thod 7400B. The safety through prudent economic feasibility as aken pursuant to an tion (OSHA). OTHER decisions also vary. The tive applicability to the I Industrial Hygienist. we used. Ventilation rates res, local exhaust ventilatio nmended exposure limits. I

Skin protection

Hand protection

Other

Respiratory protection

Thermal hazards



General hygiene considerations

Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance	
Physical state	Solid.
Form	Sheets or Pressed fibrous material panel
Color	Not available.
Odor	Not available.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Flash point	Not available.
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
10. Stability and reactivity	
Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.

 Material name:
 INSWOOL 2300 PAPER;
 INSWOOL 2300 PLEATED MODULES;
 INSWOOL 2300 VENEERING MODULES
 SDS US

 5819, 687B, 676B, 0411, 268C, 449B, 0525, 0223, 096B, 367A, 440A, 726C
 Version #: 02
 Revision date: 05-18-2021
 Issue date: 0
 4 / 7

Wear appropriate chemical resistant gloves.

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits.

Wear appropriate thermal protective clothing, when necessary.

Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents. Incompatibility is based strictly upon potential theoretical reactions between chemicals and may not be specific to industrial application exposure.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

TT. TOXICOlOgical informat		
Information on likely routes of e	xposure	
Inhalation	Prolonged inhalation may be harmful.	
Skin contact	No adverse effects due to skin contact are expected.	
Eye contact	Direct contact with eyes may cause temporary irritation.	
Ingestion	Expected to be a low ingestion hazard.	
Symptoms related to the physical, chemical and toxicological characteristics	Direct contact with eyes may	cause temporary irritation.
Information on toxicological effe	ects	
Acute toxicity	Not known.	
Skin corrosion/irritation	Prolonged skin contact may c	ause temporary irritation.
Serious eye damage/eye irritation	Direct contact with eyes may	cause temporary irritation.
Respiratory or skin sensitizatior	ı	
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	This product is not expected t	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	Suspected of causing cancer.	
	Evaluation of Carcinogenicity	
Aluminosilicate Refractor 142844-00-6)		2B Possibly carcinogenic to humans.
	d Substances (29 CFR 1910.1	001-1052)
Not regulated.	ogram (NTP) Report on Carcin	ogone
Glass, Oxide, Chemicals		Reasonably Anticipated to be a Human Carcinogen.
Reproductive toxicity		o cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	Not classified.	
Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard	Not an aspiration hazard.	
Chronic effects	Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.	
12. Ecological information	l	
Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.	
Persistence and degradability	No data is available on the de	egradability of any ingredients in the mixture.
Bioaccumulative potential	No data available.	
Mobility in soil	No data available.	
Other adverse effects		ntal effects (e.g. ozone depletion, photochemical ozone creation n, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions	This product, in its present state, when discarded or disposed of, is not a hazardous waste according to Federal regulations (40 CFR 261.4 (b)(4)). Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria for hazardous waste.
Hazardous waste code	Since this product is used in several industries, no Waste Code can be provided by the supplier. The Waste Code should be determined in arrangement with your waste disposal partner or the responsible authority.
Waste from residues / unused products	Not available.
Contaminated packaging	Not available.

14. Transport information

DOT

Not regulated as dangerous goods.

ΙΑΤΑ

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not applicable. Annex II of MARPOL 73/78 and the IBC Code

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. Toxic Substances Control Act (TSCA) Section 12(b) - This product has been assigned a CAS number; however, it is an "article" under TSCA and therefore exempt from listing on the TSCA inventory. All chemical substances in this product are listed on the TSCA chemical substance inventory where required.

Not regulated. CERCLA Hazardous Substance List (40 CFR 302.4) Not listed. SARA 304 Emergency release notification Not regulated. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052) Not regulated. Superfund Amendments and Reauthorization Act of 1986 (SARA) SARA 302 Extremely hazardous substance Not listed. SARA 311/312 Hazardous Yes chemical **Classified hazard** Carcinogenicity categories SARA 313 (TRI reporting) **Chemical name** CAS number % by wt. Aluminium Oxide (Non-Fibrous) 1344-28-1 2.5 - 10Other federal regulations Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List Not regulated. Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130) Not regulated. Safe Drinking Water Act Not regulated. (SDWA)

US state regulations

California Proposition 65

WARNING: This product can expose you to Glass, Oxide, Chemicals, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Glass, Oxide, Chemicals (CAS 65997-17-3) Listed: July 1, 1990 US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Glass, Oxide, Chemicals (CAS 65997-17-3)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	No

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	08-30-2017
Revision date	05-18-2021
Version #	02
Disclaimer	This information is based on our present knowledge on creation date. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.
Revision information	This document has undergone significant changes and should be reviewed in its entirety.